



FLAMESHIELD LOCKABLE FIRE RETARDANT NOTICEBOARDS

Board core substrate is fire rated material and is both stable and hard wearing. Fabric cover is fire rated. Aluminium frame is anodised and has rounded safety corners. The fire rated PETG locking hinged door is virtually shatterproof. The internal clearance between door and board surface is 20mm. Single door models can be fixed either portrait style or landscape and door is hinged to the long edge. Twin door models can only be fitted landscape. Wall fixings are included. This product is guaranteed for 2 years. Top hinged version also available at an additional cost.

Technical Information

- Surface/Area size (mm): 900x600, 1200x900, 1200x1200, 1800x1200, 2400x1200
- Size Depth(mm): 40
- Internal Clearance(mm): 20
- Frame Material: Anodised Satin Silver Aluminium
- Core Material: 9.5mm FlameShield Fire Panel
- Door Material: PETG
- Colour Options: See colour chart
- Fabric/Surface Options: Accents Fabric
- Weight (kg): 6-24kg
- Fire Proof: Class 0 (B) - Substrate, Class 1Y Door
- British Made: Yes
- FSC/Recycled: Yes, Board core
- Guarantee: 2 years
- More sizes available on special order: Yes

Call: 01234 676767

Email: sales@officescreens.co.uk



BOARD FELT COLOURS



ORANGE



GOLD



LAVENDER



LILAC



PLUM



LIGHT BLUE



LIGHT GREEN

Standards: Bonded Textile Noticeboard Core Certified to BS 476 Part 6 and 7 Class 0,
Bonded Textile Noticeboard Core Certified to BSEN 13501 Class B-s1-d0
Lockable Door Certified to BS 476 Part 7 Class 1Y